全国服务热线(TEL): 4006-555-379
National Service Hotline (TEL):4006-555-379
E-mail:market@hjclean.com.

FL—100型风量仪
FL—100 air flow hood













产品特点:
PRODUCT FEATURES:

鸿基洁净 FL-100 风量仪(罩)为鸿基生产,目前根据用户反映,又完成了改进型,更贴近用户的要求改进的 FL-100 具有三大特点:

1. 电池供电一次使用 30 个小时,可充电;
2. 有带轮子的可调式托架,代替人的举托,总高度可达 3M ,使风量测量更轻松。(选购)
3. 可储存 1000 个风口的测量数据,可随意翻阅、删除、打印和记录。

According to user feedback, an improved version has been completed, which is meet user requirements;
This product has three main characteristics:
1.The battery can support continuous operation for 30 hours and can be recharged.
2.There is an adjustable bracket with wheels, which can replace the lifting of a person.
3.It can store the measurement data of 1000 air vents, and can freely browse, delete print, and record.

性能参数:
PERFORMANCE PARAMETERS:

项目 Project	参数 Parameter	
使用标准 Use standars	2010版GMP 2010 version of GMP	ISO14644,FDA,EU,GMP
目标客户 Target customers	医药、航空、电子、健康、食品等 Medicine, aviation, electronics, health, food, etc	
基本技能 Basic skills	4.3英寸显示屏，蓝牙打印，电池可工作30小时，断电后不会丢失数据 It features a 4.3 - inch display screen, Bluetooth printing functionality. The battery can last for 30 hours, and data will not be lost in case of power outage.	
测试范围 Test range	200-3500m³ /h	
相对湿度范围 Relative humidity range	全量程±5%F.S Full scale ±5%F.S (Full Scale)	
储存能力 Storage capacity	自动存储1000个风口的风量值 Automatically store the air volume values of 1000 air vents	
温度范围 Temperature range	5-35℃	
相对湿度 Relative humidity	15%-70%严禁测量腐蚀性气体 15% -70% It is strictly forbidden to measure corrosive gases	
防风罩 Windshield	570*570mm,1套，830*830mm，1 套 570*570mm,1 set，830*830mm，1 set	
开启方式 Opening method	手动按钮无线遥控器 Manual button wireless remote control	
打印方式 Printing method	外置无线热敏打印机1台 1 external wireless thermal printer	
充电电池 Rechargeable battery	7.2V	
通讯 Communication	USB数据导出 USB data export	
重量 Weight	4kg（包括电池和570取样盖） 4Kg (including battery and 570 sampling cover)	